


**Svasatori multitaglienti**


Ø testa max.	mm	8	12,5	16	20
Codice		F 7790 0008	F 7790 0125	F 7790 0016	F 7790 0020
<b>F 7790</b>	Cad. €				
Ø min. di svasatura	mm	1,5	2	3,2	5
Gambo Ø	mm	8	8	10	10
Taglienti	n°	5	5	7	7
Lunghezza totale	mm	48	48	56	60


**Svasatori a tre taglienti - A 60°**


Temperati e rettificati di precisione  
Per acciaio, ghisa, metalli leggeri e leghe non ferrose





Ø testa max.	mm	8	10	12,5	16	20	25
Codice		F 7790 5008	F 7790 5010	F 7790 5125	F 7790 5016	F 7790 5020	F 7790 5025
<b>F 7790/5</b>	Cad. €						
Ø min. di svasatura	mm	2	2,5	3,2	4	5	6,3
Gambo Ø	mm	6	6	8	10	10	10
Lunghezza totale	mm	50	50	56	63	67	71

**Svasatori a tre taglienti - A 90°**


Per acciaio, ghisa, metalli leggeri e leghe non ferrose




F 7791/1 - 

F 7791/3 - 

Ø testa max.	mm	5	6	6,3	8	8,3	10	10,4	12,4	13,4	15	16,5	16,5	20,5	23	25	31
Codice	F 7791 ....	1005	1006	1063	1008	1083	1010	1104	1124	1134	1015	1165	1166	1205	—	1025	1031
<b>F 7791/1</b>	Cad. €														—		
Codice	F 7791 ....	—	3006	3063	3008	—	3010	—	3124	—	3015	—	3165	3205	3023	3025	3031
<b>F 7791/3</b>	Cad. €	—				—		—		—		—					
Ø min. di svasatura	mm	1,5	1,5	1,5	2	2	2,5	2,5	2,8	2,9	3,2	3,2	3,2	3,5	3,8	3,8	4,2
Gambo Ø	mm	4	5	5	6	6	6	6	8	8	10	8	10	10	10	10	12
Lunghezza totale	mm	40	45	45	50	50	50	50	56	56	60	60	60	63	67	67	71

F 7791/5 - **NORMEX**® - Esecuzione lunga

Ø testa max.	mm	6,3	8,3	10,4	12,4	15	16,5	20,5	25
Codice		F 7791 5063	F 7791 5083	F 7791 5104	F 7791 5124	F 7791 5015	F 7791 5165	F 7791 5205	F 7791 5025
<b>F 7791/5</b>	Cad. €								
Ø min. di svasatura	mm	1,5	2	2,5	2,8	3,2	3,2	3,5	3,8
Gambo Ø	mm	5	6	6	8	10	10	10	10
Lunghezza totale	mm	85	85	88	108	110	112	115	118

F 7791/7 - HSS Co 5% per INOX

F 7791/9 - HSS per ALU



F 7791/7 - Per INOX



F 7791/9 - Per alluminio

Ø testa max.	mm	6,3	8,3	10,4	12,4	15	16,5	16,5	20,5	25	31
Codice		F 7791 7063	F 7791 7083	F 7791 7104	F 7791 7124	F 7791 7015	F 7791 7165	F 7791 7166	F 7791 7205	F 7791 7025	F 7791 7031
<b>F 7791/7</b>	Cad. €										
Codice		F 7791 9063	F 7791 9083	F 7791 9104	F 7791 9124	—	F 7791 9165	F 7791 9166	F 7791 9205	F 7791 9025	F 7791 9031
<b>F 7791/9</b>	Cad. €					—					
Ø min. di svasatura	mm	1,5	2	2,5	2,8	3,2	3,2	3,2	3,5	3,8	4,2
Gambo Ø	mm	5	6	6	8	10	8	10	10	10	12
Lunghezza totale	mm	45	50	50	56	60	60	60	63	67	71